

Data sheet

valid from: 7/11/23



Type 2100

Flow:

- Installs into pipe sizes: 0.5 in, DN15 Hose size: DN8, 1/4 in, DN10, 3/8 in, DN15, 0.5 in
- Operating range: 0.38 to 38 lpm, 0.8 to 10 gpm
- Max Pressure rating: 16 bar @ 20 °C, 232 psi @ 68 °F
- Power source: 5 to 24V DC, 1.5mA max
- Compatibility: 8900, 9900, 9900-1BC, 9950
- *End connector kits must be ordered separately. See accessories
- *-H version can be used with flare fitting. Flow range: 3 - 27 lpm

	MFR #	Body	Process Con- nection	Communica- tion Interface	Operating Range	Description
*	3-2100-1L	PVDF	Thread	Open Collector Frequency	0.38 to 3.8 lpm	FKM o-ring
*	3-2100-2L	PVDF	Thread	Open Collector Frequency	0.38 to 3.8 lpm	EPDM o-ring
*	3-2100-1H	PVDF	Thread	Open Collector Frequency	3 to 38 lpm	FKM o-ring
*	3-2100-2H	PVDF	Thread	Open Collector Frequency	3 to 38 lpm	EPDM o-ring

	MFR #	Flow Range	Code
*	3-2100-1L	0.38-3.8 lpm (0.10-1 gpm)	159 000 001
*	3-2100-2L	0.38-3.8 lpm (0.10-1 gpm)	159 000 003
*	3-2100-1H	3.0-38.0 lpm (0.8-10 gpm)	159 000 002
*	3-2100-2H	3.0-38.0 lpm (0.8-10 gpm)	159 000 004

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

PT PROFILTER INDONESIA

Ruko Blok G/54 – Gudang A/01 Jl.Canadian Broadway

Kawasan Pergudangan Commpark – Kotawisata – Cibubur

Phone : +6221 84937329 Email : sales@profilterindonesia.com